

## TECHNICAL DATA DIGEST

### CHROMALL

|              |   |
|--------------|---|
| DESCRIPTION: | A vinyl toluene super high gloss aerosol enamel formulated to provide a high luster chrome-like finish. Makes chrome look like new.   |
| BASIC USES:  | Chromall spray paint is a fast drying aerosol. Ideal for touchup or the entire job. Useful to protect cars, boats, bumpers, furniture, bicycles, shutters, toys, louvered doors, etc. |
| FINISH:      | High luster chrome - like finish.   |
| PACKAGING:   | 11 ounces can   |
| COLOR:       | Chrome  |

### TECHNICAL DATA

|                  |                              |
|------------------|------------------------------|
| VISCOSITY:       | 10-15 seconds (Ford Cup #4)  |
| FLASH POINT:     | Less than 156 <sup>0</sup> F |
| SOLIDS (WEIGHT): | 13.61%                       |
| SOLIDS (VOLUME): | 5.43%                        |
| GLOSS:           | Metallic bright dry          |
| DRYING TIME:     | 20 min. max.                 |

### DRY FILM

|            |                        |
|------------|------------------------|
| THICKNESS: | .75 mils. (calculated) |
|------------|------------------------|

## TECHNICAL DATA DIGEST

### CHROMALL

#### SURFACE

##### PREPARATION:

Surface must free of dirt, grease, silicones, etc. Protect surrounding areas with newspapers, drop cloth, etc.

#### NEW METAL

##### SURFACES:

Prime steel or iron with Spray Primer. Allow 30 min. to recoat when using Spray Primer.

#### PREVIOUSLY

##### PAINTED SURFACES:

Make sure surface is free of all oil, grease, dirt, rust and peeled or blistered paint to restore back to sound surface. Spot prime bare areas with Aerosol Primer before applying finish coat of Chromall.

#### SURFACES IN

##### GOOD CONDITION:

Apply Chromall aerosol liberally on bare areas until obtaining a smooth coating. Primers are not necessary.

#### SURFACES IN

##### POOR CONDITION:

Prime affected areas on metal or wood with Rust Chem Aerosol Primer. Allow 2 hours for best drying and spray on surface to obtain a high luster chrome finish.

#### APPLICATION:

Protect surrounding areas with newspapers, drop cloth, etc. Can temperature should be between 70<sup>0</sup> F and 80<sup>0</sup> F. Shake can vigorously for at least one minute after mixing ball rattles. Hold can 12" to 16" from surface to be painted and direct opening in spray button at object. Press spray button firmly using steady, even strokes while spraying. It is recommended that you spray two or three thin coats for best results. Clean spray button immediately after use by turning cap upside down and pressing button until no more paint comes out.

## TECHNICAL DATA DIGEST

### CHROMALL

#### CAUTIONS:

**EXTREMELY FLAMMABLE.** Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Keep away from heat, sparks and flames. Use only with adequate ventilation. Do not use in basement or other unventilated areas. If you must use it indoors, open windows and doors to ensure a continuous flow of fresh air during application drying. In case of eye contact, flush with large amounts of water for at least 15 minutes. Get medical assistance. **KEEP OUT OF REACH OF CHILDREN.**