

## TECHNICAL DATA DIGEST

### HARRIS CLASSIC GOLD SPRAY PAINT

DESCRIPTION: Harris Paints Classic Gold Spray Paint can be used on metal, wood, or almost any other surfaces, indoor or outdoors. This high quality acrylic spray enamel leaves a beautiful, durable, protective glossy finish and prevents rust on metal surfaces.

FINISH: Metallic bright finish

PACKAGING: 11 ounces can

#### TECHNICAL DATA

VISCOSITY: 10-15 seconds (Ford cup #4)

FLASH POINT: Less than 156<sup>o</sup> F

SOLIDS (WEIGHT): 16.46%

SOLIDS (VOLUME): 6.28%

GLOSS: Metallic bright

DRYING TIME: 15 min. max.

#### DRY FILM

THICKNESS: 0.75 mils. (calculated)

#### APPLICATION

SURFACE PREPARATION: Thoroughly clean all grease, oil, dirt, wax and rust scale from surface before painting.

NEW METAL SURFACES: New or rusted areas should be primed with Aerosol Primer before painting.

PREVIOUSLY PAINTED SURFACES: Make sure surface is free of dirt, grease, wax and rust scale from surface before painting. Use drop cloth or newspapers to protect surrounding areas from spray mist. Surface temperature must be above 65<sup>o</sup> F from painting. Do not paint in high winds or excessively high humidity.

## TECHNICAL DATA DIGEST

### HARRIS CLASSIC GOLD SPRAY PAINT

#### SURFACES IN

#### GOOD CONDITIONS:

Spray directly on bare areas. Primers are not necessary.

#### SURFACES IN

#### POOR CONDITIONS:

Remove all rust and peeled or blistered paint to restore back to sound surface. Prime all surfaces with Spray Primer, allow 30 min. to dry.

#### APPLICATION:

Shake can until agitator ball begins to rattle and continue to shake for one min. after. Occasionally shake during use. Hold can 12 to 16 inches from surface to be sprayed and apply several thin coats rather than one heavy coat. Recoat after one hour.

#### CAUTIONS:

**EXTREMELY FLAMMABLE.** Keep away from heat, sparks, flames or other heat sources. Vapors may ignite explosively. Prevents buildup vapor. Do not smoke. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection or leave the area. **KEEP OUT OF THE REACH OF CHILDREN.**