

HARRIS®

Guard House Paint

Basic Uses: interior/exterior wood surfaces

OIL PAINT



TECHNICAL DATA

VISCOSITY: 80-85 Ku's
 WEIGHT/GALLON: 9.70 ± 0.10 lbs/gal
 FLASH POINT: Below 100°F
 SOLIDS (WEIGHT): 50%
 SOLIDS (VOLUME): 33%
 DRY FILM THICKNESS: Recommended film thickness 2.0 mils

SIZES

1 gallon (3.785 Liters)
 5 gallon (18.925 Liters)

FINISH

Gloss (85% @ 60°)

COLOR

White
 Pastel Base

DESCRIPTION

An oil base interior-exterior paint developed for use in the tropics on new or previously painted wood surfaces. Also useful as a finish coat on primed metal or masonry. It combines economy with good coverage, lasting protection and decoration.

COMPOSITION AND PROPERTIES

A long-oil alkyd base finish coat which features easy brushing, good hiding, good color retention, excellent resistance to weather and moisture and mildew resistance on the paint film only.

APPLICATION

SURFACE PREPARATION:

All surfaces should be clean, dry and free of chalk and all contaminants. Dirt and dust must be removed with a stiff bristle brush and by compressed air. Oil and grease should be removed by cleaning with Mineral Spirit.

NEW SURFACE:

Prime with this paint to which has been added 1 pint of mineral spirits; allow 48 hours to recoat. Iron and Steel-Prime with HARRIS® Rust Chem Metal Primer; allow overnight to recoat. Galvanized and Aluminum → prime with HARRIS® Galvanized Metal Primer; allow 24 hours to dry to recoat. Masonry → prime with Titanium Wall Primer; allow 24 hours to

recoat.

PREVIOUSLY PAINTED SURFACES:

Remove all grease, oil, and peeling paint, and foreign material. Spot prime bare area with recommended primer. Sheltered areas must be washed and sanded. Mildewed areas should be washed with water containing 16 fluid oz. of liquid household bleach and 2 fluid oz. of detergent per gallon. Rinse with clean water and let dry. Areas that are heavily weathered and/or in poor condition shall have all cracked, loose, or peeling paint thoroughly removed. If there is a past history of blistering, remove all old paint and treat like new wood.

METHOD OF APPLICATION:

Stir thoroughly before and during application. Paint always on shaded side of building. Do not dilute Guard House Paint, use as supplied. Use Nylon or bristle brush, short nap roller, or spray. Two coats are recommended on all surfaces for best results and full gloss development. On sound, repainted surfaces, one (1) coat may be sufficient.

COVERAGE: 600 sq. ft. per gallon, depending on surface texture and porosity.

DRYING (NORMAL CONDITIONS): To touch in one (1) hour; to touch up in four (4) hours. These periods will be extended on cool or humid days. Allow (12) hours to recoat.

CLEANUP: Use warm, soapy water immediately.

PRECAUTIONS

KEEP FROM FREEZING! Do not apply when surface or air temperature is below 50° (10°C). Stop painting at least two (2) hours before you expect heavy dew or the temperature to drop below 50°F (10°C). Use only with adequate ventilation. Close container after each use.

CAUTION: Do not take internally. In case of eye contact, flush thoroughly with water. Do not rub eye. In case skin contact, flush area immediately with clean water.

KEEP OUT OF THE REACH OF CHILDREN.