

HARRIS®

Wall Primer

Basic Uses: new & existing interior/exterior surfaces

WALL PRIMER



TECHNICAL DATA

VISCOSITY: 75-80 KU'S (KREBS-STORMER)
FLASH POINT: Non-flammable
DENSITY: 11.30 Lbs
GRIND: 6 NS min
SOLIDS (WEIGHT): 50.23%
SOLIDS (VOLUME): 37.81%

SIZES

5 gallons
1 gallon

FINISH

Flat 0-5% @
Geometry 60°

COLOR

White

DESCRIPTION

Harris Acrylic Wall Primer is an alkali resistant surface conditioner based on styrene acrylic resin. It provides a barrier coat for high pH surface. It also seals the surface preventing moisture to affect the finish coat, and avoid premature failures. It is recommended as a primer for new concrete surfaces, stucco, concrete, block, mortar joint surfaces, gypsum board and to seal loose chalk, in light condition, on previously painted surfaces. This primer is also sealer designed to consolidate light chalk and concrete dust on the surface, allowing a non-penetrating coating to adhere properly. Retards efflorescence and promote good paint adhesion.

APPLICATION

All surfaces should be sound, clean and free of oil, grease, loose or peeling paint, and other foreign substances before painting. All surfaces previously coated with cement base water paints, should be washed before applying Titanium Acrylic Wall Primer. Can be applied over light chalky surfaces.

Clean mildewed surfaces by scrubbing with water containing 16 oz. household

bleach and 2 oz. liquid detergent per gallon of water. Then, follow procedure as for new surfaces.

To insure complete mixing stir thoroughly. Apply uniformly with brush, roller or spray. Porous or texture surfaces will require more primer. Avoid application in direct sun or on hot surfaces.

THINNING:

Not normally recommended. Do not mix with solvent or solvent thinned paints.

DRYING TIME:

To touch: 10-15 minutes
To recoat: 1 hour

COVERAGE:

350-400 sq. ft. per gallon, depending on surface texture and porosity. Porous or texture surfaces will require more primer.

CLEAN UP:

Wipe up drips and spatters with a wet cloth with soap and water; clean equipment with soapy water.

PRECAUTIONS

Do not apply if temperature of air or surface is below 50°F (10°C). **Harmful if swallowed. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush**

area immediately with clean water. Do not take internally. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN!