

HARRIS®

SUPER-X SEMI-GLOSS ACRYLIC

Basic Uses: interior/exterior surfaces

ACRYLIC PAINT



TECHNICAL DATA

VISCOSITY: 105-110 KU's
FLASH POINT: Non-flammable
SOLIDS (WEIGHT): 53% (varies with colors)
SOLIDS (VOLUME): 39% (varies with colors)
DRY FILM THICKNESS:
1.4 mils dry recommended
DRYING TIME: Set to touch in 15 minutes
Allow 4 hrs. to recoat.

SIZES

5 gallons (18.927 Liters)
1 gallon (3.785 Liters)

FINISH

Flat 2-5% @
Geometry 60°

COLOR

White
Bone White
Bases: Pastel, Tint,
Deep, Accent

DESCRIPTION

This product is a revolutionary non-yellowing exterior/interior finish, specifically formulated as a high quality, semi-gloss paint for use on properly primed wallboard, wallpaper, wood, plaster and masonry. Offers a lasting beauty and protection on surfaces that are subjected to daily abuse and frequent washing such as kitchens, bathroom walls and hallways. It may also be used over primed metal surfaces. Super-"X" Acrylic Latex Semi-Gloss meets Federal Specification TT-P-1511B.

COMPOSITION AND PROPERTIES

This product is based on an acrylic latex which provides excellent resistance to weathering. Use of light-fast pigments provide excellent retention. Easy to apply. Mildew resistance on paint film, plus excellent resistance to blistering, cracking and peeling among others.

APPLICATION

All surfaces must be clean and free of oil, grease, chalk, other foreign matter, loose or peeling paint and loose or granular materials.

NEW SURFACES:

Concrete, stucco, and structural block prime with HARRIS® Ever Grip Acrylic Super Wall Primer. Wood countersink nail

heads. Caulk nail heads and joints or cracks with latex type caulk. Shellac all knots and sap streaks. Sand rough areas and wipe clean. Prime entire surface with HARRIS® Titanium Wall Primer. For Steel, prime with HARRIS® Red Oxide Primer. For Galvanized Steel or Aluminum-clean with solvent and prime with HARRIS® Galvanized Metal Primer.

PREVIOUSLY PAINTED SURFACES:

Can be used over either oil or latex painted surfaces. Either surface must be clean to obtain proper adhesion. Sand any glossy areas and dust clean. Wipe away dirt and chalk. Clean and spot prime any failed areas. Use soap and water on overhead areas such as eaves and ceilings to remove invisible residues, a major cause of peeling in these areas. Rinse clean and allow drying. Apply first coat with a good quality roller or brush and avoid excessive brushing or spreading too thinly. If you use a roller we recommend a synthetic cover. Allow first coat to dry and apply a second coat using a brush, roller or spray.

METHOD OF APPLICATION:

Nylon or polyester brush, roller or spray. On sound, repainted surfaces, one (1) coat is usually sufficient. Certain shades of oranges, yellow and pinks may require a second coat for uniform color. Maintain a wet edge at all time. If touch-up is required after enamel has set, wait until

it has thoroughly dried. Use two (2) coats of Titanium Waterborne Enamel for maximum color uniformity and durability. Do not paint in damp, frosty or cold weather. Do not apply too heavily.

THINNING: None normally needed. For spray, thin with up to 1 pint (473 ml) per gallon (3.785 liters) of paint. Do not add mineral spirits or solvent- thinned paints.

CLEANUP: Clean up drips, spatters and equipment with clean rags and water.

COVERAGE: 300 – 500 sq. ft. per gallon, depending on application, surface texture and/or porosity.

PRECAUTIONS

Do not apply if temperature of air or surface is below 50°F (10°C). **Harmful if swallowed. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water.** Do not take internally. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN!