



TRAFFIC PAINT WATER BASED

Basic Uses: exterior for concrete & asphalt floors

MARKING



TECHNICAL DATA

VISCOSITY: 75-85 KU's
FLASH POINT: Non-flammable
PIGMENT (WEIGHT): 60%
NON-VOLATILE VEHICLE (WEIGHT): 46%
DRY FILM THICKNESS:
DRYING TIME: 20-25 mins.

SIZES

1 gallon (3.785 Liters)
5 gallons (18.927 Liters)

FINISH

FLAT

COLOR

Yellow
White
Blue (1gallon only)

DESCRIPTION

A high grade, fast drying and durable product for marking traffic lanes on highways and cross streets, curbs, parking areas, safety zones and storage spaces in airports, factories, warehouses, service stations, terminals and markets.

Conforming to the U.S Bureau of Publics Roads specified colors, this products is ready to use in most conventional marking equipment.

COMPOSITION AND PROPERTIES

Acrylic Latex based enamel for marking purposes which provides fast drying, resulting in minimum maintenance time and minimum interruptions in traffic movements. Within minutes it forms a tough film with excellent adhesion to substrate; resistance to water, oils, and wear..

APPLICATION

SURFACE PREPARATION: Remove all oil, dirt, rust, grease, etc. by appropriate means.

PREVIOUSLY PAINTED SURFACES: Remove all oil, grease, dirt, rust and peeled or blistered paint back to sound surface. Sand glossy areas and dust clean.

METHOD OF APPLICATION: Brush or short nap 1/4" (6.35mm) roller.

THINNING: Thin the first coat on bare concrete with one (1) pint of water per gallon. In other cases, no thinning is required. Do not add oils or solvents.

CLEAN UP: Wipe off drips and spatters using a wet cloth with soap and water. Clean equipment with soapy water

COVERAGE: The calculated spreading rate for this product is 15 gallons per mile of standard 4-inch strip, or 350 linear feet of standard 4-inch strip per gallon at an average wet film of 0.014 in.

PRECAUTIONS

Do not apply if temperature of air or surface is below 50°F (10°C). Stop painting at least two (2) hours before you expect dew to form, rain or the temperature to drop.

CAUTION! Flammable Product Keep out of Flames and Sparks contains aromatic solvents. Do not take internally. Close container after each use. **KEEP OUT OF THE REACH OF CHILDREN.**

(Continued)

