



TRAFFIC PAINT PREMIUM YELLOW

Basic Uses: exterior for concrete floors



TECHNICAL DATA

VISCOSITY: 70-90 KU's
FLASH POINT: >80° F
SOLIDS (WEIGHT): 50%
SOLIDS (VOLUME): 74%
DRY FILM THICKNESS:
1.4 mils dry recommended
DRYING TIME: Set to touch in 20 mins.

SIZES

1 gallon (3.785 Liters)
5 gallons (18.927 Liters)

FINISH

FLAT

COLOR

Yellow

DESCRIPTION

A fast drying alkyd solvent base traffic marking paint with excellent durability when applied to highways and cross streets, curves, parking areas, safety zones and storage spaces in airports, factories, warehouses, service stations, terminals and markets.

COMPOSITION AND PROPERTIES

Short oil alkyd resin solvent borne traffic paint with fast drying characteristics, good adhesion to all type of roadway surfaces, included concrete, asphalt, stone and brick.

APPLICATION

SURFACE PREPARATION: Remove all oil, dirt, rust, grease, etc. by appropriate means.

PREVIOUSLY PAINTED SURFACES: Remove all oil, grease, dirt, rust and peeled or blistered paint back to sound surface. Sand glossy areas and dust clean.

METHOD OF APPLICATION: Brush or short nap 1/4" (6.35mm) roller.

THINNING: Thin the first coat on bare concrete with one (1) pint of water per gallon. In other cases, no thinning is

required. Do not add oils or solvents.

CLEAN UP: Clean up drips, spatters and equipment with clean rags and Harris Lacquer Thinner.

COVERAGE: Approximately 500 sq. ft. per gallon depending on method application and surface porosity.

PRECAUTIONS

Do not apply if temperature of air or surface is below 50°F (10°C). Stop painting at least two (2) hours before you expect dew to form, rain or the temperature to drop

CAUTION! Flammable Product Keep out of Flames and Sparks contains aromatic solvents. Do not take internally. Close container after each use. **KEEP OUT OF THE REACH OF CHILDREN.**



(Continued)

Tung • O • Var Marine Clear Spar Varnish

