

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

1. Identification

1.1. Product identifier

Product Identity

Premium Flat Bases

CODE:

17101, 17102, 17103, 17104, 17105, 17106, 17107, 17108

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

Harris Paints Company
PO Box 364723
San Juan, P.R. 00936-4723

Emergency

CHEMTREC (USA)

(800) 424-9300

Customer Service: Harris Paints Company

787-798-1005

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Carc. 1A;H350

May cause cancer.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H350 May cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P281 Use personal protective equipment as required.

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

[Response]:

P308+313 IF exposed or concerned: Get medical advice / attention.
P391 Collect spillage.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Titanium dioxide CAS Number: 0013463-67-7	20 - 30	Not Classified	[1][2]
calcined china clay CAS Number: 0092704-41-1	5.0 – 15	Not Classified	[1]
FLUXCALCINED DIATOMACEOUS EARTH CAS Number: 0068855-54-9	1.0 - 10	Not Classified	[1]
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate CAS Number: 0025265-77-4	1.0 - 10	Not Classified	[1]
Quartz CAS Number: 0014808-60-7	0.10 - 1.5	Acute Tox. 4;H332 STOT RE 2;H373 Carc. 1B;H350	[1][2]
Propylene Glycol CAS Number: 0000057-55-6	0.10 – 1.0	Not Classified	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Make sure to remove any contact lenses from eyes before rinsing. Flush with large quantities of water for 15 minutes.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

Ingestion

Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Get medical attention immediately. provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

4.2. Most important symptoms and effects, both acute and delayed

Overview

No specific symptom data available.

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: May cause hazardous fumes when heated to decomposition. Fumes may contain carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of metals listed in section II. Fumes may also contain oxides of nitrogen.

5.3. Advice for fire-fighters

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool. Cool containers exposed to flames with water until well after the fire is out. Protective equipment for fire-fighters.

Due to pressure build-up, closed containers exposed to extreme heat may explode. During emergency conditions, over-exposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

None

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet with water and mix.

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

Collect adsorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local state and federal hazardous regulation before disposing into approved hazardous waste landfills. Obey relevant law.

7. Handling and storage

7.1. Precautions for safe handling

Use non-sparking utensils when handling this material.

Ground all equipment when handling flammable solvent borne materials; smoking is strictly prohibited in areas where this materials are used. Use impermeable aprons and protective clothing whenever to prevent skin contact. The use of head caps whenever possible is strongly recommended.

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Avoid inhalation of vapor's and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Alkaline materials, strong acids and oxidizing materials.

Avoid hot metal surface. Keep away from excessive heat and open flames. KEEP OUT OF REACH OF CHILDREN.

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep containers tightly closed. Keep upright. Store separated from: Oxidizing material. Alkalis. Acids. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labeled container.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0013463-67-7	Titanium dioxide	OSHA	TWA 15 mg/m ³
		ACGIH	TWA: 10 mg/m ³ 2B, Revised 2006,
		NIOSH	Footnote ca
		Supplier	No Established Limit
0014808-60-7	Quartz	OSHA	No Established Limit
		ACGIH	TWA: 0.025 mg/m ³ A1, 1
		NIOSH	0.05 mg/m ³ TWA (respirable)
		Supplier	No Established Limit
0025265-77-4	2,2,4-trimethyl-1,3-pentanediol	OSHA	No Established Limit

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

	monoisobutyrate	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0068855-54-9	FLUXCALCINED DIATOMACEOUS EARTH	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0092704-41-1	calcined china clay	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000057-55-6	Propylene Glycol	OSHA	No Established Limit
		ACGIH	TWA(Aerosol): 10 mg/m3
		NIOSH	No Established Limit
		Supplier	10 mg/m3 TWA (listed as AIHA WEEL)

Carcinogen Data

CAS No.	Ingredient	Source	Value
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0014808-60-7	Quartz	OSHA	Select Carcinogen: No
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025265-77-4	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068855-54-9	FLUXCALCINED DIATOMACEOUS EARTH	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0092704-41-1	calcined china clay	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000057-55-6	Propylene Glycol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

When spraying this material use a NIOSH approved cartridge respirator or gasmask suitable to keep airborne mists and vapor concentration below threshold limit values. When using in poorly ventilated and confined spaces, use a fresh air supplying respirator or a self-contained breathing apparatus.

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

- Eyes** Use chemical safety glasses, goggles, and face shields for eye protection.
- Skin** Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended. Chemical resistant gloves.
- Engineering Controls** General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.
- Other Work Practices** Ensure showers and eyewash stations are available. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Liquid
Odor	Low Odor
Odor threshold	Not determined
pH	8.5 – 9.2
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	-44-390 F
Flash Point	Not Measured
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 2.4 (in air by volume) Upper Explosive Limit: 17.4 (in air by volume)
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	1.35 (H ₂ O=1)
Solubility in Water	Soluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity Brookfield	105-111 Ku's
VOC Content	40 g/L

9.2. Other information

No other relevant information.

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.

10.5. Incompatible materials

Alkaline materials, strong acids and oxidizing materials.

10.6. Hazardous decomposition products

May cause hazardous fumes when heated to decomposition. Fumes may contain carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of metals listed in section II. Fumes may also contain oxides of nitrogen.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	No data available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate - (25265-77-4)	3,200.00, Rat - Category: 5	15,200.00, Rabbit - Category: NA	No data available	No data available	No data available
Quartz - (14808-60-7)	No data available	No data available	No data available	No data available	No data available
Propylene Glycol - (57-55-6)	20,000.00, Rat - Category: NA	20,800.00, Rabbit - Category: NA	105.00, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	1A	May cause cancer.
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Harmful to aquatic life.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Titanium dioxide - (13463-67-7)	Not Available	Not Available	Not Available
calcined china clay - (92704-41-1)	Not Available	Not Available	Not Available
FLUXCALCINED DIATOMACEOUS EARTH - (68855-54-9)	Not Available	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate - (25265-77-4)	Not Available	Not Available	Not Available
Quartz - (14808-60-7)	Not Available	Not Available	Not Available
Propylene Glycol - (57-55-6)	40,613.00, Oncorhynchus mykiss	18,340.00, Ceriodaphnia dubia	19,000.00 (96 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: NO		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D2A

US EPA Tier II Hazards

Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Safety Data Sheet

Premium Flat

SDS Revision Date:

05/28/2015

Benzenedicarbonitrile, 2,4,5,6-tetrachloro-
Diuron
Quartz
Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Titanium dioxide

Pennsylvania RTK Substances (>1%):

FLUXCALCINED DIATOMACEOUS EARTH

Titanium dioxide

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H332 Harmful if inhaled.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

To the best of our knowledge, the information contained here is accurate, obtained from sources believed to be accurate. We neither guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsibility of the user.

End of Document