

HARRIS®

Titanium Dry Eggshell 3 in 1: Primer, Paint & Sealer

Basic Uses: 100% acrylic for interior/exterior surfaces

ACRYLIC PAINT



TECHNICAL DATA

VISCOSITY: 102-110 KU'S (KREBS-STORMER)
WEIGHT/GALLON: 11.07 ± 0.5 lbs.
FLASH POINT: Non-flammable
SOLIDS (WEIGHT): 55%
SOLIDS (VOLUME): 45%
EMULSION: Acrylic Polymer
DRY FILM THICKNESS: At a rate of 125
ft²/gal: 5 mil dry, 12.5 mils wet
PIGMENT (by weight): 33% ± 1%

SIZES

5 gallons
1 gallon

FINISH

Low Gloss 6-12% @
Geometry 60°

COLOR

Bases: White/Pastel,
Tint, Deep

DESCRIPTION

TITANIUM DRY EGGSHELL is a high performance alkali resistant water-proofing eggshell paint, with a revolutionary new technology of ultra small particle size hydrophobic latex designed to water-proof a wide variety of surfaces. Ultra White, ready mix paint tintable to pastel colors using HARRIS® designer Colors. For exterior/interior (above or below grade use).

COMPOSITION AND PROPERTIES

Titanium Dry is composed mainly of hydrophobic acrylic latex and chalk resistance Titanium Dioxide. Upon the many properties Titanium Dry waterproofs concrete, brick, basements, concrete blocks, stucco, foundations, retaining walls, water ponds.

APPLICATION

Stir thoroughly before and during application. Paint always on shaded side of building. Do not dilute TITANIUM DRY, use as supplied. Do not apply when surface or air temperature is below 50 °F or if rain is

expected within 4 hours.

NEW SURFACES:

Apply TITANIUM DRY directly on bare concrete (do not use any primer). Apply first coat with a good quality roller or brush, working TITANIUM DRY into the pores of the masonry. Avoid excessive brushing. Allow to dry 4 hours and apply a second coat using a brush, roller or spray.

PREVIOUSLY PAINTED SURFACES:

Apply directly to properly prepared surface (do not use any primer). Apply first coat with a good quality roller or brush and avoid excessive brushing or spreading too thinly. If you use a roller we recommend a synthetic cover. Allow first coat to dry 4 hours and apply a second coat using a brush, roller or spray.

DRYING TIME:

To touch: 1 hour
To recoat: 5 hour
To cure: 24 hours

COVERAGE:

Smooth Surface: First Coat 100 ft²/gal and second coat 125 ft²/gal
Rough Surface: First Coat 75 ft²/gal and second coat 125 ft²/gal

PRECAUTIONS

Harmful if swallowed. Contains Acrylic

Resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. Do not take internally. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN!