



WOOD CARE

PRODUCT  
IMAGE

# Teak Sealer

Basic Uses: interior/exterior wood surfaces

## TECHNICAL DATA

VISCOSITY: 10-12 sec. Ford Cup#4  
FLASH POINT: <20°F TCC  
DENSITY (lbs/gal): 6.75 ± 0.5  
ODOR: Strong aromatic solvent odor.

## SIZES

1 gallon (3.785 Liters)  
1 quart (.95 Liters)  
½ pint (236 ML)

## FINISH

## COLOR

Liquid Clear

## DESCRIPTION

### PRODUCT DESCRIPTION:

A penetrating clear water repellent and wood preservative for use on exterior or interior unpainted wood such as Imbuia, Pine, Oak, Mahogany, Plywood, etc. This product will preserve and protect wood.

### BASIC USES:

This product will preserve and protect wood. It will bring out the beauty and richness of natural wood or stain previously applied. It helps control swelling and retard normal deterioration and discoloration.

## APPLICATION

Stir before use. Thinning is not recommended. Apply using brush or roller. Two coats are recommended.

### COVERAGE:

One gallon covers 500-600sq.ft. depending on surface porosity and method of application.

### DRY TIME:

Under normal conditions, the film should be dry for handling after two hours.

## PRECAUTIONS

**CAUTION! Combustible. HARMFUL IF INHALED**

**Keep away from heat and open flame. Do not smoke. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation.**

**Do not take internally.**

**KEEP OUT OF THE REACH OF CHILDREN.**