

HARRIS®

PORCH & PATIO ANTISLIP FLOOR PAINT

Basic Uses: interior/exterior for wood, metal and concrete

ENAMEL



TECHNICAL DATA

VISCOSITY: 75-80 KU's
FLASH POINT: Non-flammable
SOLIDS (WEIGHT): 43% (varies with colors)
SOLIDS (VOLUME): 31% (varies with colors)
DRY FILM THICKNESS:
1.4 mils dry recommended
DRYING TIME: Set to touch in 1 hour
Allow 2 hrs. to recoat and 18 hrs. for traffic

SIZES

1 gallon (3.785 Liters)

FINISH

SATIN SHEEN

COLOR

Various (6)

DESCRIPTION

High performance 100% acrylic anti-slip latex enamel, formulated to promote additional safety when walking. It is easy to apply on potentially dangerous areas and will resist heavy traffic. Ideal for interior and exterior wood, metal and concrete floors on porches, decks, patios, steps, basements, etc..

COMPOSITION AND PROPERTIES

A 100% acrylic paint with an additive to bring texture.

APPLICATION

SURFACE PREPARATION: All surfaces must be clean and free of oil, grease, chalk, other foreign matter, loose or peeling paint and loose or granular materials.

NEW SURFACES: New concrete floors should be aged at least 30 days before painting. Old bare concrete floors must be cleaned prior to paint. The old concrete floor could be cleaned using a solution of made by mixing 1 part of CROSSCO muriatic acid with 3 parts of water. Be careful handle the acid and the acid solution with rubber gloves due to corrosive behavior of the acid. Wood must be weathered at least 60 days prior to painting.

PREVIOUSLY PAINTED SURFACES: Remove loose or loosely adhering paint. Repair major voids. Dull all glassy areas

by sanding and dust clean.

METHOD OF APPLICATION: Buy enough paint to complete the entire job and intermix all gallons of the same color to insure color uniformity. Stir gently. Apply liberally; roll out no more than a 2 ft. area with a full 9 inch roller. Let dry 4 hours and apply end coat.

THINNING: No thinning is required. Do not add oils or solvents.

WASHING: Do not wash or let water sit on painted surface before 14 days to permit proper curing or finish. May be washed after 14 days with detergent and soft cloth or sponge mop, then rinse. Do not use abrasive cleaners.

COVERAGE: On smooth surfaces, 400-500 sq. feet per gallon. On rough or porous surfaces coverage will be reduced.

PRECAUTIONS

Do not apply if temperature of air or surface is below 50°F (10°C). Stop painting at least two (2) hours before you expect dew to form, rain or the temperature to drop. KEEP FROM FREEZING!.

CAUTION! Do not take internally. Close container after each use. **KEEP OUT OF THE REACH OF CHILDREN.**

(Continued)

